Product #: 383572 Name: CELATOM SP GRADE (PAPER) Desc: From: BRENNTAG MID-SOUTH INC. To: Wednesday, March 10, 2010



MATERIAL SAFETY DATA SHEET

Page 1 of 4

1 - MATERIAL IDENTIFICATION

Material Name:

Celatom FW-12, FW-14, FW-18, FW-20, FW-40, FW-50, FW-60,

FW-70, FW-80, SP

Supplier / Manufacturer Identification: EP Minerals, LLC.

9785 Gateway Drive, Suite 1000

Reno, Nevada 89521

Phone Number: (775) 824-7600

Emergency Telephone Number: (775) 824-7600

2 - COMPOSITION / INFORMATION ON INGREDIENTS

 Chemical Name
 Wt %
 CAS #

 Diatomaceous earth, Flux calcined
 100%
 68855-54-9

 Crystalline silica, Cristobalite
 35 – 50%
 14464-46-1

3 - HAZARDS IDENTIFICATION

Breathing dust containing crystalline silica over a prolonged period of time may cause lung damage. Crystalline silica (quartz, cristobalite) is a known cause of silicosis. Avoid breathing dust (see Section 11 for additional information).

4 - FIRST AID MEASURES

4.1 Inhalation: Remove to fresh air.

4.2 Ingestion: Short-term exposure not considered harmful. Drink water to reduce bulk and drying effects.

4.3 Eyes: Wash with generous quantities of water. Consult physician if irritation persists.

4.4 Skin: None necessary. If dryness occurs, use moisture renewing lotions.

5 <u>- FIRE FIGHTING MEASURES</u> 5.1 Flashpoint and Method:	Not applicable	Non-Flammable
5.2 Flammable Limits:	Not applicable	Non-Flammable
5.3 Autoignition Temperature:	Not applicable	Non-Flammable
5.4 Flammable Class:	Not applicable	Non-Flammable
5.5 Flame Propagation or burning rate of solids:	Not applicable	Non-Flammable
5.6 General Hazard:	Not applicable	Non-Flammable
5.7 Extinguishing Media:	None	Non-Flammable
5.8 Hazardous Combustion Products:	Not applicable	Non-Flammable
5.9 Fire Fighting Procedures:	Not applicable	Non-Flammable
5.10 Fire Fighting Equipment:	Not applicable	Non-Flammable
5.11 Sensitive to Static Discharge:	Not applicable	Non-Flammable
5.12 Sensitivity to Impact:	Not applicable	Non-Flammable

Product #: 383572 Name: CELATOM SP GRADE (PAPER) Desc:

From: BRENNTAG MID-SOUTH INC. To: Wednesday, March 10, 2010

Celatom FW-12, FW-14, FW-18, FW-20, FW-40, FW-50, FW-60, FW-70, FW-80, SP

Page 2 of 4

6 - ACCIDENTIAL RELEASE MEASURES

6.1 Environmental Precautions: Diatomaceous earth is a non-toxic, non-biodegradable mineral.

Waste generated from this product would only be considered hazardous when mixed with a substance that would be considered

hazardous.

6.2 General Procedures: No special procedures necessary

6.3 Release Notes: No special procedures necessary

7 - HANDLING & STORAGE

7.1 Handling: Use appropriate personal protective equipment as specified in Section 8.

Handle and use in a manner consistent with good industrial practice.

7.2 Storage: Store unopened containers in a dry place.

8 - EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Engineering Controls: Control dust to within the ACGIH-TLV with local ventilation.

8.2 Occupational exposure limits: <u>EXPOSURE LIMITS TABLE</u>

Quartz mg/m³ Cristobalite mg/m³

ACGIH - TLV 0.025 0.025

8.3 Personal Protective Equipment:

Respiratory: Respirators fitted with filters certified to NIOSH (US) standard 42CFR84 under series N95 should be

worn when airborne dust is present.

Skin: Not normally necessary

Eyes & Face: Not normally necessary

9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical State: Solid

9.2 Odor: Odorless

9.3 Appearance: Light pink to white powder

9.4 pH (10% slurry): 10

9.5 Color: Light pink to white

9.6 Boiling point: Not applicable

9.7 Melting point: > 1300°C

9.8 Oxidizing properties: Not applicable

9.9 Vapor pressure: Not applicable

9.10 Density: 2.3

9.11 Solubility in water: < 1%

9.12 Coefficient oil/water: Not applicable

9.13 Other data: None

Product #: 383572 Name: CELATOM SP GRADE (PAPER) Desc:

From: BRENNTAG MID-SOUTH INC. To: Wednesday, March 10, 2010

Celatom FW-12, FW-14, FW-18, FW-20, FW-40, FW-50, FW-60, FW-70, FW-80, SP

Page 3 of 4

10 - STABILITY and REACTIVITY

10.1 Conditions to avoid: Hydrofluoric acid

10.2 Stability: Stable

10.3 Hazardous decomposition products: Not applicable

10.4 Other considerations: None

11 - TOXICOLOGICAL INFORMATION

11.1 Dermal LD₅₀: Not available

11.2 Oral LD₅₀: Not available

11.3 Inhalation LC₅₀: Not available

11.4 Eye effects: May cause significant irritation to the eye

11.5 Skin effects: May cause dryness

11.6 Sensitization: Not available

11.7 Chronic: Flux-calcined diatomaceous earth (Kieselguhr) is composed of amorphous and crystalline silica. Amorphous silica is not classifiable as carcinogenic to humans. Crystalline silica, when inhaled as respirable dust, has been classified as carcinogenic to humans over prolonged and sustained exposure. Long-term inhalation of respirable crystalline silica may contribute to the respiratory disease "silicosis", a non-cancerous lung disease. In a 1997 monograph (Volume 68, "Silica"), the International Agency for Research on Cancer (IARC) concluded that overall the epidemiological findings support increased risk of lung cancer from inhaled crystalline silica resulting from occupational exposure (classified in Group 1), while there was inadequate evidence in humans for the carcinogenicity of amorphous silica (classified in Group 3).

12 - ECOLOGICAL INFORMATION

12.1 Environmental Data: Insoluble mineral product. Will not have adverse impact on waterways.

12.2 Ecotoxicological information: Not applicable

12.3 Chemical fate information: Not applicable

13 DISPOSAL CONSIDERATIONS

13.1 Disposal method: Use solid waste disposal common to landfill operations. Not considered

hazardous waste.

13.2 Product disposal: Avoid creating dust.

13.3 Empty container: Avoid creating dust.

13.4 General comments: None

Product #: 383572 Name: CELATOM SP GRADE (PAPER) Desc:

From: BRENNTAG MID-SOUTH INC. To: Wednesday, March 10, 2010

Celatom FW-12, FW-14, FW-18, FW-20, FW-40, FW-50, FW-60, FW-70, FW-80, SP

Page 4 of 4

14 - TRANSPORT INFORMATION

14.1 DOT (Department of Transportation):

A. Proper shipping name

B. Technical name

Not restricted by DOT

Diatomaceous earth

C. Label Use product identifier (trade name) with Technical name below.

14.2 Canada Transport of Dangerous Goods:

A. Proper shipping name

B. Technical name

Not restricted

Diatomaceous earth

C. Label Use product identifier (trade name) with Technical name below.

15 - REGULATORY INFORMATION

15.1 WHMIS Hazard Symbol & Classification



- Class D, Division 2, Subdivision A
- Chronic toxic effect by inhalation
- WHMIS toxic and WHMIS controlled

15.2 Canada – Ingredient Disclosure List

This product does not have any ingredient(s) on the Ingredient Disclosure List.

15.3 Canada - Environmental Protection Act - Product listed on Domestic Substance List.

15.4 This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

16	– OTHER	INFORMATION

NFPA CODES: Fire: 0 Health: 1 Reactivity: 0

HMIS CODES: Fire: 0 Health: * Reactivity: 0 Protection: E

* Refer to data on Material Safety Data Sheet

Preparation Date of MSDS

Prepared by: Peter Lenz – Director, Research & Development

Telephone Number: (775) 824-7600

Date: July 1, 2007

Disclaimer: As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.